



DOCUMENT 383-95

METEOROLOGY GROUP

**CATALOG OF
ATMOSPHERIC ACOUSTIC
PREDICTION MODELS**

**WHITE SANDS MISSILE RANGE
KWAJALEIN MISSILE RANGE
YUMA PROVING GROUND
DUGWAY PROVING GROUND
COMBAT SYSTEMS TEST ACTIVITY**

**ATLANTIC FLEET WEAPONS TRAINING FACILITY
NAVAL AIR WARFARE CENTER WEAPONS DIVISION
NAVAL AIR WARFARE CENTER AIRCRAFT DIVISION
NAVAL UNDERSEA WARFARE CENTER DIVISION, NEWPORT
PACIFIC MISSILE RANGE FACILITY**

**30TH SPACE WING
45TH SPACE WING
AIR FORCE FLIGHT TEST CENTER
AIR FORCE DEVELOPMENT TEST CENTER
AIR FORCE WEAPONS AND TACTICS CENTER
SPACE AND MISSILE SYSTEMS CENTER,
SPACE TEST AND EXPERIMENTATION PROGRAM OFFICE
ARNOLD ENGINEERING DEVELOPMENT CENTER**

DTIC QUALITY INSPECTED 8

**DISTRIBUTION A: APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION IS UNLIMITED**


19950719 038

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 1995		3. REPORT TYPE AND DATES COVERED	
4. TITLE AND SUBTITLE Catalog of Atmospheric Acoustic Prediction Models				5. FUNDING NUMBERS	
6. AUTHOR(S)					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Meteorology Group Range Commanders Council White Sands Missile Range, NM 88002-5110				8. PERFORMING ORGANIZATION REPORT NUMBER RCC 383-95	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) STEWS-RCC Range Commanders Council White Sands Missile Range, NM 88002-5110				10. SPONSORING / MONITORING AGENCY REPORT NUMBER same as block 8	
11. SUPPLEMENTARY NOTES New document					
12a. DISTRIBUTION / AVAILABILITY STATEMENT APPROVED FOR PUBLIC RELEASE: DISTRIBUTION IS UNLIMITED.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This document contains, in its early chapters, some background information on acoustic propagation effects, explosion characteristics, and atmospheric effects of explosions as well as a brief explanation of sonic booms and their effects. In the latter chapters, summaries and descriptions of a number of models currently in use at various member ranges have been provided.					
14. SUBJECT TERMS atmospheric acoustic prediction models				15. NUMBER OF PAGES 51	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLAS	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLAS	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLAS	20. LIMITATION OF ABSTRACT NONE		



GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

DOCUMENT 383-95

**CATALOG OF
ATMOSPHERIC ACOUSTIC
PREDICTION MODELS**

001

JUNE 1995

001

Prepared by

**METEOROLOGY GROUP
RANGE COMMANDERS COUNCIL**

Published by

**Secretariat
Range Commanders Council
U.S. Army White Sands Missile Range,
New Mexico 88002-5110**

P R E F A C E

Many range meteorology support units are required to provide predictions for acoustic overpressures resulting from high explosive and gun blasts, missile launches, and sonic booms. The Air Quality Committee of the Range Commanders Council (RCC) Meteorology Group (MG), in assessing these requirements, concluded that a catalog of available models, similar to the one published by the Office of the Federal Coordinator for Meteorological Services and Supporting Research for atmospheric transport and diffusion models, would be useful to all ranges or to organizations planning to use member ranges for an activity that could result in generation of high acoustic or blast levels.

This document contains, in its early chapters, some background information on acoustic propagation effects, explosion characteristics, and atmospheric effects of explosions as well as a brief explanation of sonic booms and their effects. In the latter chapters, summaries and descriptions of a number of models currently in use at various member ranges have been provided.

Any information from users which might assist in improving this document is appreciated. Correspondence reporting new models not incorporated in this document or changes in models already incorporated should be addressed to the Meteorology Group through the Secretariat, Range Commanders Council. The Meteorology Group Committee responsible for preparation of this document was composed of the following individuals:

Mr. H. Church, Sandia National Laboratories, Chairman
 Mr. R. Olsen, U.S. Army Research Laboratory
 Battlefield Environment Directorate
 Mr. R. Himebrook, U.S. Army Research Laboratory
 Battlefield Environment Directorate
 Mr. W. Smith, NASA - Weather Support Office
 Mr. L. Corbett, Naval Air Warfare Center Weapons Division
 Mr. E. Keppel, Air Force Development Test Center
 Mr. C. Caspersen, Naval Oceanography Command
 Mr. C. Clough, U.S. Army Combat Systems Test Activity

Additionally, the Air Quality Committee wishes to thank all who provided data for the survey, and those who reviewed the document.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

TABLE OF CONTENTS

	<u>Page</u>
PREFACE.....	iii
CHAPTER 1 - INTRODUCTION.....	1
CHAPTER 2 - ATMOSPHERIC ACOUSTIC PROPAGATION EFFECTS...	3
Effects of the Speed of Sound Profile.....	3
General Acoustic Effects.....	6
Spherical Spreading.....	6
Atmospheric Sound Absorption.....	6
Ground Impedance.....	6
Turbulence Scattering.....	7
Summary.....	7
CHAPTER 3 - EXPLOSION CHARACTERISTICS.....	9
Airblast and Noise.....	9
Close-in Airblast.....	10
Long Distance Airblast.....	13
Long Distance Noise.....	13
Refracted Atmospheric Propagation.....	15
Special Test Configurations.....	16
CHAPTER 4 - MODEL SUMMARIES.....	19

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
2-1	Sound speed profiles and their effects on acoustic propagation.....	4
2-2	Wind and temperature profiles that result in sound ducts.....	5
3-1	Peak airblast overpressure measurements from large TNT surface explosions (scaled to 1 pound of TNT at sea level and standard atmospheric conditions).....	11
3-2	Airblast peak overpressures versus ground distance for charges exploded on or near the ground surface.....	12
3-3	Long distance airblast and noise from surface (idealized, nonrefracting atmosphere).....	14
3-4	Height-of-burst multiplying factor.....	17

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1-1	UNIT CONVERSION FACTORS.....	2
3-1	TNT-EQUIVALENT WEIGHTS OF EXPLOSIVES FOR AIRBLAST PEAK OVERPRESSURE.....	9

REFERENCES

CHAPTER 1

INTRODUCTION

There are a number of member ranges currently engaged in high-explosive blast testing or activities that result in high acoustic levels and others who are anticipating such activities. These acoustic waves generated from the blast impulses could have adverse impacts on nearby communities. This document is designed to allow meteorologists, environmental engineers, and safety personnel to use models to predict acoustic overpressures and high intensity sound levels, thus predicting potential damage or nuisance to people and property. These models can serve as tools to (1) determine short-term operational predictive decisions, (2) select blast sites based on location and local climatology to determine if environmental damage criteria are likely to occur at selected distances and radials, (3) determine inputs for environmental assessment and impact statements, and (4) provide guidance in assessing the verity of damage claims resulting from high-level blasts.

The original intent of this report was to present a listing of candidate models which have been designed for operational or research and developmental use in assessing the impacts of acoustic waves from high-explosive blasts. While compiling information on the models in this document, the authors decided it would also be helpful to include some background information on the nature of high-explosive blasts and on the attendant acoustic waves along with their potential environmental impacts.

While a number of texts and documents address the topic of acoustic propagation and the environmental impacts of acoustic waves, a useful overall document we have encountered is a Defense Nuclear Agency publication entitled High Explosive Field Tests: Explosion Phenomena and Environmental Impacts. The first few sections of this report quote extensively from DNA 6187F. In particular, chapter 3, Explosive Characteristics of Airblast is taken almost verbatim from DNA 6187F.

In general, conservative assumptions regarding the magnitude of explosion phenomena and their effects are used to avoid underestimating the environmental impact of the phenomena. If significant impact is indicated, less conservative assumptions can be used in a careful analysis to provide a more realistic assessment.

A variety of measurement units is used in this report, depending on how the particular types of data are customarily given. In general, however, output for users of this document are presented in metric units, except higher explosives (HE) charge sizes which are given in TNT-equivalent weight; that is, the weight of TNT (with explosive energy of 10^9 gram calories/ton) that would produce approximately the same magnitude of a particular phenomenon as the specific explosive charge in question. Table 1-1 shows the factors to convert to other measurements systems.

TABLE 1-1. UNIT CONVERSION FACTORS

<u>To Convert</u>	<u>Into</u>	<u>Multiply by</u>
Gravitational units of acceleration (g's)	Centimeters per Second ² (cm/sec ²)	981
Cubic feet (ft ³)	Cubic meters (m ³)	2.832×10^{-2}
Cubic meters (m ³)	Cubic feet (ft ³)	35.31
Grams (g)	Pounds (lb)	2.205×10^{-3}
Pounds (lb)	Grams (g)	453.6
Feet (ft)	Meters (m)	0.3048
Meters (m)	Feet (ft)	3.281
Pascals (Pa)	Pounds per square inch (psi)	1.451×10^{-4}
Pounds per square inch (psi)	Pascals (Pa)	6894
Pound per square foot	Pascals (Pa) [Newtons per m ²]	48
Square feet (ft ²)	Square meters (m ²)	9.290×10^{-2}
Square meters (m ²)	Square feet (ft ²)	10.76
<u>Calculation</u>		
Sound Pressure Level = SPL = $(20 \log p/p_0)$ dB		
Using $p_0 = 2 \times 10^{-5}$ Pa implies SPL = $(20 \log p + 94)$ dB		
For $p = 1 \text{ lb/ft}^2 = 48 \text{ Pa}$, SPL = $(20 \log 48 + 94)$ dB = 128 dB		

CHAPTER 2

ATMOSPHERIC ACOUSTIC PROPAGATION EFFECTS

INTRODUCTION

The atmosphere is not a homogeneous fluid. Wind and temperature at different heights will usually have different values. A picture of the wind field taken at various heights above the ground at a specific time is called a wind profile. A temperature profile normally cools with increasing height above the ground. These vertical changes in wind and temperature are referred to as wind and temperature gradients. Sound propagation is refracted by wind and temperature gradients, resulting in the sound wave being bent from a straight line.

The basic problem of atmospheric acoustic propagation is the variability of the atmospheric boundary layer (ABL), also called the planetary boundary layer. The ABL is that part of the earth's atmosphere directly influenced by the presence of the earth's surface. The ABL varies in depth from as little as 100 m (328 ft.) at night to as much as 2 km (6562 ft.) or more on hot sunny days. Atmospheric sound transmission varies with time of day, prevailing weather conditions, and source/receiver orientation with respect to the wind direction or azimuth. These conditions will cause the sound levels to be enhanced or diminished from those otherwise expected. Some of the types of conditions found are based on conditions noted earlier. Sound intensities can vary as much as 30 dB in magnitude over significant distances (5 km (16 400 ft.) or more) and is caused by the variation of the speed of sound profile where, in one instance, the sound being propagated is bent over and focused toward the earth's surface and, in the other, sound is propagated upward in the atmosphere and dispersed.

EFFECT OF THE SPEED OF SOUND PROFILE

The atmosphere refracts sound well. The changes in the speed of sound with height are a function of temperature and wind. In the absence of wind, the sound speed equation is as

$$C = 331.6 \sqrt{(1+T/273)} \quad (2-1)$$

where C = sound speed in meters per second
T = temperature in degrees Celsius

The component of wind in the direction of propagation adds to the sound speed as

$$C = 331.6 \sqrt{(1 + T/273)} + W \cos \Theta$$

where W = magnitude of the wind in meters per second

Θ = the angle between the direction of propagation and the direction of the wind.

Both wind speed and temperature vary with altitude, and the resulting directed sound speed profile determines how sound will propagate in a given direction. Figure 2-1 provides examples to illustrate this point. If sound speed decreases with height, sound waves are refracted away from the ground. Conversely, if sound speed increases with height, sound waves will bend back toward the ground; even sound waves with original upward elevation may bypass obstructions because of the downward refraction.




Figure 2-1. Sound speed profiles and their effects on acoustic propagation.

A sound duct results when the speed of sound above a given level equals or exceeds that at a lower level. When the lower level is the ground, the duct is called a surface-based duct. Surface-based ducts can result from the speed of sound first decreasing and then increasing with height or just increasing with height. Typical nighttime inversions are examples of the latter case. A variety of meteorological conditions produce enhanced propagation conditions as well as decreased propagation conditions. Two kinds of meteorological conditions that result in surface-based ducts are illustrated in figure 2-2. Note that the dashed line in the temperature drawings represents the normal cooling rate with height for the atmosphere; it is called the dry adiabatic lapse rate where the temperature decreases 9.8°C for a change of 1000 m (3281 ft.) in altitude, the upper temperature picture shows a temperature inversion with a dry adiabatic lapse rate aloft. The lower picture shows heating of the air near the ground, resulting in what is called a superadiabatic lapse rate where the temperature decrease is greater than 9.8°C for each 1000 m (3281 ft.) of altitude with a dry adiabatic lapse rate aloft.




Figure 2-2. Wind and temperature profiles that result in sound ducts.

GENERAL ACOUSTIC EFFECTS

Other general acoustic effects included spherical spreading, atmospheric sound absorption, ground impedance, and turbulence scattering.

Spherical Spreading

The sound pressure level spreads spherically in the absence of wind. Spherical spreading is commonly referred to as the "1 over R spreading" ($1/R$) where R is the distance from the source. (For sound intensity or energy, use R^2 .) Another way of expressing spherical spreading is for each doubling of distance from a source, the sound pressure decreases by 6 dB. (The 3-dB decrease represents one-half the previous value.) If there are 10 doublings of distance from 1 m (3.3 ft.) to 1024 m (3360 ft.) (1, 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024), a decrease of 60 dB results from the source sound strength. Various authors have stated that a quiet countryside has a background sound pressure level of about 10 dB (reference pressure is 2×10^{-5} Pa), and a typical city has a background sound pressure level of about 60 dB indicating that in the absence of ducting or forward refraction a 130-dB source could be heard approximately 4 km (13,000 ft.) in a city environment, and this same source will be heard 8 km (26,000 ft.) if the signal-to-noise ratio is increased by 6 dB. On the other hand, a 90-dB sound should be audible less than 1/2 km (1600 ft.), unless there is a significant wind to transport the sound.

Atmospheric Sound Absorption

The atmosphere absorbs sound energy; however, this effect is not a significant factor for sound of less than 500 Hz. For instance, at 10 Hz approximately 0.04 dB is lost to absorption over a 10 km (33,000 ft.) path, while at 100 Hz about 3.5 dB is lost. By contrast, a 1000 Hz sound would lose approximately 100 dB over a 10 km (33,000 ft.) path. What is important is the blast impulse from a large weapon firing or explosion is not greatly absorbed by the atmosphere, because the frequency content of the energy is primarily at the lower frequencies, less than 0.5 Hz.

Ground Impedance

Ground impedance, as used in outdoor acoustics, is a measurement of the extent to which an acoustic or blast wave traveling in the atmosphere would be absorbed into the ground upon contacting it. The acoustic energy that is not absorbed by the ground is reflected back into the atmosphere. The condition where most of the acoustic energy of a given frequency is absorbed by the ground is called low impedance. Soft sands like those found at beaches or fresh powdery snow are examples of a low impedance surface. Medium impedance surfaces reflect a majority of the acoustic energy that strikes the ground with the amount of absorption being a function of the frequency content of the acoustic energy.

Medium impedance grounds provide an adequate surface for long range propagation of acoustic energy in a surface duct. Most of the lands of the United States are classified as a medium impedance surface for low frequencies; those less than 200 Hz. High impedance surfaces reflect all or almost all of the acoustic energy striking on them. Water and concrete surfaces and mountains with rock outcroppings are examples of high impedance surfaces and would reflect all the energy. Therefore, attention should be paid to the surface type the energy would be propagating over, whereby higher impedance surfaces could result in greater propagation distances because of little energy loss from reflected acoustic waves.

Turbulence Scattering

Turbulence created by thermals or wind flow over the terrain causes sound to be scattered into shadow zones or zones of silence created by the atmospheric refraction paths. The degree that turbulence effects the propagation of acoustic energy is not well understood but is presently the subject of intense investigation through modeling and data collection efforts. Some data collected to date indicate that turbulence may be able to cause amplitude variation as great as 6 to 10 dB depending on the turbulence conditions.

SUMMARY

The ability of the atmosphere to transport sound is dependent on the meteorological conditions between the source and receiver. Any combination of wind and temperature profiles that result in a sound duct provides an enhanced condition for long range sound propagation. Sound energy may be depleted as it travels through the atmosphere and interacts with the ground. Scattering of sound by turbulence causes amplitude and phase variations resulting in variance of the sound about some mean level. Ground impedance affects the sound amplitude levels of the absorption of sound striking a soft sandy surface and the reflection of a sound wave off a concrete or water surface. For sound with frequencies below 200 Hz, spherical spreading is the primary cause for sound reduction over medium or high impedance surfaces. Sound can be enhanced or decreased by refraction causing the focusing of sound towards the surface or upward into the atmosphere.

CHAPTER 3

EXPLOSION CHARACTERISTICS OF AIRBLAST

INTRODUCTION

The detonation of a charge of high explosive near the earth's surface produces airblast and noise, a crater, ejecta and missiles, ground shock, explosive products, and buoyant clouds that will carry dust and explosive products downwind. This section addresses the magnitude of airblast and noise estimated for explosive charge weights ranging for 454 to 454,000 kg (1/2 to 500 tons, typical for field tests) exploded on or near the ground surface.

AIRBLAST AND NOISE

Airblast (the explosion shock wave in air) is usually of greatest concern in HE field tests, because damage can occur at relatively long distances from the explosion. Damage is caused by various airblast mechanisms but is usually related to the peak overpressure of the airblast wave. Table 3-1 shows TNT-equivalent weight factors for some explosives. The airblast phenomena discussed in this section include close in airblast, long distance airblast and noise, and refracted atmospheric propagation.

TABLE 3-1. TNT-EQUIVALENT WEIGHTS OF EXPLOSIVE
FOR AIRBLAST PEAK OVERPRESSURE

Explosive Type	TNT-Equivalent Weight Factor ^a	Explosive Type	TNT-Equivalent Weight Factor ^a
TNT	1.00	RDX-Cyclonite	1.17
Tritonal	1.07	Nitromethane	1.00
Nitroglycerine	1.23	Ammonium Nitrate	0.84
Pentolite	1.42	Black Powder	0.46
PETN	1.27		

^aTo determine the TNT-equivalent weight of an explosive, multiply the weight of the explosive by the equivalent weight factor, e.g., at a given distance, 1 ton of ammonium nitrate is required to produce the peak overpressure equivalence to that from 0.84 ton of TNT.

Source: Event DIAL PACK Preliminary Report, Volume 1

Close-in Airblast

Figure 3-1 shows measured values of airblast peak overpressure as functions of distance for four field tests in which large, semihemispherical charges of TNT were detonated on the ground surface. The measurements have been adjusted to convert all results to 1 pound of TNT at sea level and standard atmospheric conditions. As can be seen, these results agree very well and were predictable. Also, except for charges elevated significantly above the earth's surface (at least tens to hundreds of feet for charge sizes of interest), figure 3-1 is a slightly conservative estimate of airblast overpressure. Field tests conducted at higher altitudes result in peak overpressures somewhat less than those indicated in figure 3-1. Burying a charge also tends to reduce the peak overpressures. Thus it can be assumed that, except for significantly elevated charges, the airblast overpressure will not be greater than indicated by figure 3-1.




Figure 3-1. Peak airblast overpressure measurements from large TNT surface explosions (scaled to 1 pound of TNT at sea level and standard atmospheric conditions).

The distance at which any particular peak overpressure occurs varies in proportion to the cube root of the charge weight; for example, increasing a charge weight by a factor of 8 increases the ground distance for a given overpressure by a factor of 2 (cube root of the charge weight). The curves shown in figure 3-2 for typical weights of field test HE charges are obtained from figure 3-1 by plotting overpressures of environmental concern (below 140 kPa (20 psi)) versus the product of ground distance and the cube root of the charge weight.




Figure 3-2. Airblast peak overpressures versus ground distance for charges exploded on or near the ground surface.

Long Distance Airblast

As the peak overpressure decreases at increasing distances from the explosion, the airblast front slows down to a speed approaching the speed of sound. As the airblast approaches an acoustic wave, it is refracted by temperature and wind-speed gradients in the air. At distances where the airblast peak overpressure is less than approximately 2.5 kPa (0.4 psi), meteorological conditions usually predominate to cause anomalous propagation; airblast is refracted toward or away from the ground resulting in peak overpressures either greater or less than would occur in a nonrefracting atmosphere. Peak overpressures at long distances may vary by an order of magnitude or more depending on whether the meteorological conditions are favorable or unfavorable. Long-distance airblast is of concern because very low peak overpressures can crack windows and cause excessive noise.

Based on a large amount of empirical data, relationships have been formulated for estimating the overpressure at long distances from explosions. For a large chemical explosion on or near the ground surface with the airblast propagating through a homogeneous, nonrefracting atmosphere, the peak overpressure at long distances near the ground surface is approximately

$$\Delta p = 668 (2W)^{0.37} D^{-1.1} (P/P_0)^{0.63} \quad (3-1)$$

where

Δp = incident peak overpressure (Pa)

W = TNT-equivalent weight of the explosive charge (tons) (The factor of 2 is to account for ground surface producing distant blast pressures equivalent to those from a free-air burst about double in size.)

D = Distance from the explosion (km)

P = Ambient atmospheric pressure at the test site (mb)

P_0 = Standard sea-level atmospheric pressure (1000 mb)

Equation 3-1 is plotted in figure 3-3 for explosive yields of interest at standard sea-level ambient atmospheric pressure.

Long Distance Noise

An explosion produces impulsive, predominantly low-frequency sound of sufficient intensity to be heard at long distances. The measure of sound intensity is the unweighted Sound Pressure Level (SPL) expressed in decibels (dB), which are dimensionless units proportional to the square of the pressure ratio (relative to a reference pressure of 2×10^{-5} Pa):

$$\text{SPL}(\text{dB}) = 20 \log_{10}(\Delta p / 0.00002) = 20 \log_{10}(\Delta p) + 94 \quad (3-2)$$

where Δp = peak pressure change in Pa. The sound level in decibels are shown on the right-hand scale of figure 3-3.




Figure 3-3. Long distance airblast and noise from surface (idealized, nonrefracting atmosphere).

Explosive charges produce a sound energy spectrum that is predominately low frequency at distances of interest, approximately 10 Hz or less for large charges. The energy concentration is displaced toward the low end as explosive yield increases. Also at greater distances, the spectrum is displaced toward lower frequencies as higher frequencies undergo greater attenuation and the shock wave loses its impulsive characteristics. At long distances, the sound of an explosion is often a rumble.

Refracted Atmospheric Propagation

Vertical gradients of wind and temperature in the atmosphere will refract low-pressure airblast. A decrease in temperature with altitude (the usual daytime condition) refracts airblast away from the ground, so the overpressure at a given ground distance will be less than shown in figure 3-3 for the case of no refraction. Conversely, an increase in temperature with altitude or an inversion refracts airblast toward the ground, thus increasing the overpressure that would be expected at a given ground distance. An increase in wind speed with altitude (the usual condition) refracts upwind airblast away from the ground and downwind airblast toward the ground, thus tending to increase downwind overpressures and decrease upwind overpressures. Conversely, decreasing wind speeds with altitude tend to refract upwind airblast toward the ground and downwind airblast away from the ground, which tend to increase peak overpressures upwind and decrease peak overpressures downwind. The combined effects of wind and temperature variations with altitude must be considered when analyzing long range propagation of airblast and noise.

The standard atmosphere (temperature decreasing with altitude) and no wind corresponds to a weak gradient condition; that is, overpressures will be somewhat less than indicated by figure 3-3. With a strong gradient, that is, rapid decrease of temperature with height, overpressures vary approximately inversely with the square of the distance resulting in strong refraction away from the ground and greatly reduced distant blast pressures. To reduce the possibility of window breakage by airblast, gradient conditions are usually sought and obtained when detonating a large explosive charge in a field test.

The meteorological conditions that lead to amplification of long distance airblast and the relative location and magnitude of such amplification are summarized from a large amount of data. The three conditions of concern are (1) boundary layer ducting and focusing, (2) jet stream ducting and focusing, and (3) downwind ozonosphere propagation.

In a temperature inversion, warm air overlies cooler air near the ground surface with the result that acoustic waves are trapped and ducted to propagate along the ground. The magnification of overpressure at distances is further enhanced in the downwind direction because of normal downward refraction resulting from the usual condition of increasing wind speed with altitude. Based on the available data, it appears inversion or downwind conditions may produce boundary layer ducting that enhances the unrefracted overpressures shown in figure 3-3 by a factor of 3 or more.

The jet streams (high speed winds at several tens of thousands feet altitude) can strongly refract acoustic waves back to the earth. Amplification of the peak overpressure by somewhat less than an order of magnitude can be expected where such refracted waves are focused back to the earth's surface. Typically, such focusing occurs approximately 65 to 85 km (40 to 50 miles) away, in the direction of the jet stream flow.

In northern temperate climates, winds at altitudes of about 50 km (30 miles) usually blow from east to west in summer and west to east in winter. Since temperature and sound speed at 50 km (30 miles) altitude are near their values at ground surface, the result is enhanced blast pressures approximately 200 km (125 miles) downwind from these high altitude winds and reduced blast pressures upwind.

As indicated by the previous discussion, the long distance airblast magnitude at any particular point can vary by more than an order of magnitude, depending on the particular meteorological conditions. Under some meteorological conditions, a relatively small explosive charge can produce airblast at long distances in excess of that from a large charge exploded under gradient conditions. The prediction of the pattern of long distance airblast and noise magnitudes on the ground requires specialized skills and meteorological measurements that are normally part of field tests. The scheduling of field tests to reduce the possibility of window breakage is based on such measurements and predictions with the result that little damage has occurred from previous large field tests.

Special Test Configurations

The preceding discussion applies for most test configurations, where the charge is exploded relatively near the ground surface. A significantly elevated or buried charge can produce different magnitudes of airblast than shown in figures 3-2 and 3-3.

Exploding a charge at a shallow depth-of-burst may increase airblast magnitude at long distances because of more efficient conversion of explosive energy to shock energy when an explosion is confined. The assumption of no reduction in airblast or noise from burying a charge is usually warranted for environmental assessment. If this assumption indicates that significant environmental damage may occur from close-in airblast and if the depth-of-burst is deeper than about one charge radius, it may be desirable to have the airblast phenomena calculated by a specialist who can include depth-of-burst effects.




Figure 3-4. Height-of-burst multiplying factor.

When a charge is exploded above the ground surface, shock waves reflected from the ground surface merge with the direct shock wave to enhance the magnitude of the peak overpressure at any given distance. As shown in figure 3-4, the effect of elevating a charge is to make it appear that the charge is increased in weight. At the optimum height-of-burst for airblast enhancement, a charge appears to be increased in weight approximately 2.8 times so that the distance to a given overpressure (by cube root scaling) is about 1.5 times that from a charge of the same height exploded on the ground surface. Height-of-burst is measured from the center of gravity of the explosive charge to the ground surface; therefore, zero height-of-burst means the charge is half buried in the ground.

Figure 3-4 can be used to estimate the increase in airblast magnitude for an elevated charge. The product of the TNT-equivalent charge weight and the multiplying factor should be used in figures 3-2 and 3-3 to estimate the airblast magnitude as a function of distance. Substantial elevation is required to significantly extend the distance of a given peak overpressure. For example, a 900 kg (1 ton) charge would have to be elevated approximately 20 m (60 ft.) above ground level to extend a given overpressure 10 percent farther.

If more than one charge is exploded at nearly the same location and time so that the shock waves interact, the airblast environment is complex. Outside the array of charges and depending on the distance (as shown with the MISERS BLUFF multicharge event), the airblast may appear as a series of explosions or as a single explosion of larger size than any of the individual explosions. The conservative assumption for a distant blast is that the individual shocks will merge to produce a single shock equivalent to that from a single charge with a weight equal to the sum of the weights of the individual charges and located at the center of the array.

CHAPTER 4

MODEL SUMMARIES

This chapter contains summaries of acoustic models which have been identified through personal contact and through literature searches. Developers and current points of contact are provided when known. Information on application, inputs, processes, and outputs are also provided within very general guidelines. Limitations and additional comments are provided as required.

There are two types of models used to calculate sound pressure levels. The first is ray trace which uses a refractive equation to define the propagation, and the second is an analytical method which uses the wave equation to determine acoustic transmission losses. Any of the various models listed in this catalog are variations of the above and depend on various assumptions and the amount of detail specified in making the calculations. For example, all of the models calculate transmission loss caused by spherical spreading and absorption. Very few can be used to calculate turbulence and ground impedance which can have an appreciable effect on the sound pressure level. The more rigorous treatment of losses are computed using the wave equation; however, they are much more complex and require much greater computer resources. The ray trace models lose their accuracies at the lower frequencies, because the sound speed may vary over the wavelength of the propagating sound. In the case of impulse noise, this loss of accuracy could be minimized using empirical data where transmission loss for blasts are calculated using the ANSI standard S2.20-1983, Airblast Characteristics for Single Point Explosions in Air With a Guide to Evaluation of Atmospheric Propagation and Effects.

In dealing with high altitude explosions, the same refractive atmosphere has to be taken into account. The bending of rays now takes place at much higher altitudes by the troposphere, and for very large explosions, the refracting effects take place in the stratosphere, 20 to 45 km (65,620 to 147,645 ft.). In these latter cases, the propagation path takes place over many hundred of kilometers.

In the case of large blast explosions, the pressure levels are measured with microbarographs and the unit of measurement is in pascals (Pa) or pounds per square inch (psi) over pressure. For continuous noises or small blasts, the pressure levels are measured with microphones and the unit of measurement is dBm of acoustic energy.

NAME OF MODEL: ASOPRAT

DEVELOPER: University of Mississippi

POINT OF CONTACT: Dr Hank Bass

Address: Acoustic Laboratory
Univ. of Mississippi, MS 38677

Phone Number: (601) 232-5840

Fax: (601) 232-7494

TYPE: Operational ☐ Research ☒ Other ☐

TYPE OF SOURCE: Point ☒

Above Ground ☒

Surface ☒ Buried ☐

Sonic Boom ☐

Moving on Surface ☐

APPLICATIONS: Blast ☐ Sonic Boom ☐ Moving Source on Surface ☐
Other Source on Surface

LIMITATIONS: ☐

THEORY: Ray Trace ☐ Full Wave ☐ Empirical ☐ Other Hybrid, ray trace & full wave

METEOROLOGICAL INPUT: Sfc Temp ☐ Surface Winds ☐ Surface Pressure ☐
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☐ Other ☐

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other Sound pressure in dB

OUTPUT TYPE: Numerical ☒
Specific Azimuth ☐ Ranges ☒
dB ☒ Other ☐

Graphic ☒

Contours ☒

dBX ☒ Other ☐

ADDITIONAL COMMENTS:

Survey updated: 31 Aug 94

NAME OF MODEL: BLASTC (used for either flat or uneven terrain)

DEVELOPER: ACTA Inc.

POINT OF CONTACT: Mr Alan Bodner

Address: ACTA Inc, 23430 Hawthorne Blvd, Suite 300
Torrance, CA 90505-4723

Phone Number: (310) 378-6254

Fax: (310) 375-0663

TYPE: Operational X Research Other

TYPE OF SOURCE: Point X

Above Ground Surface X Buried

Sonic Boom Moving on Surface

APPLICATIONS: Blast X Sonic Boom Moving Source on Surface
Other

LIMITATIONS:

THEORY: Ray Trace X Full Wave Empirical Other

METEOROLOGICAL INPUT: Sfc Temp Surface Winds Surface Pressure
Vert Temp Profile Vert Wind Profile
Rawin Data X Other Tower & DASS

OUTPUT UNITS: Overpressure in Pascals Overpressure in PSI X
Percent Broken Windows X
Other Expected casualties

OUTPUT TYPE: Numerical X

Specific Azimuth X Ranges X
dB Other

Graphic

Contours Limited (requires additional graphic software to
interface with BLASTC output)

dB Other

ADDITIONAL COMMENTS: FORTRAN 77 - PC
Ada: UNIX workstation

Survey updated: 29 Aug 94

NAME OF MODEL: BLASTMAP

DEVELOPER: US Army CERL Acoustic Team

POINT OF CONTACT: Michael J. White

Address: US Army Construction Engineering Research Lab
PO Box 9005, Champaign, IL 61826-9005

Phone Number: (217) 352-6511 ext 7436

Fax: (217) 373-7251

TYPE: Operational ☐ Research ☐ Other Environmental Assessment

TYPE OF SOURCE: Point X

Above Ground X Surface X Buried X

Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast X Sonic Boom ☐ Moving Source on Surface ☐
Other ☐

LIMITATIONS: ☐

THEORY: Ray Trace ☐ Full Wave X Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp X Surface Winds X Surface Pressure ☐
Vert Temp Profile X Vert Wind Profile X
Rawin Data ☐ Other ☐

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other Sound Exposure Level

OUTPUT TYPE: Numerical X
Specific Azimuth ☐ Ranges ☐
dB ☐ Other ☐
Graphic X
Contours X
dB X Other ☐

ADDITIONAL COMMENTS: Uses Operational Data from Range.

Survey updated: 21 Sept 94

NAME OF MODEL: BLASTO Ver 9

DEVELOPER: Mr Jack Reed

POINT OF CONTACT: Mr Jack Reed

Address: JWR Inc, 5301 Central Ave, NE, Suite 220

Albuquerque, NM 87108

Phone Number: (505) 265-6550

Fax: (505) 255-2946

TYPE: Operational X Research X Other

TYPE OF SOURCE: Point X

Above Ground X

Surface X Buried X

Sonic Boom

Moving on Surface

APPLICATIONS: Blast X Sonic Boom Moving Source on Surface
Other

LIMITATIONS:

THEORY: Ray Trace Full Wave X Empirical X Other

METEOROLOGICAL INPUT: Sfc Temp X Surface Winds X Surface Pressure X

Vert Temp Profile X Vert Wind Profile X

Rawin Data X Other Standard Atmosphere

OUTPUT UNITS: Overpressure in Pascals X Overpressure in PSI

Percent Broken Windows X (when shot point & target locations specified. Target window survey are entered in the target list file, or an estimate of pane counts is made from census population report entries (19 panes per capita). When no weather or target list is provided, a window breakage probability is provided as a function of overpressure in the overpressure-distance tables. When weather and target are provided, window breakage is calculated for the target and its weather-dependant overpressure.

Other SI Units

OUTPUT TYPE: Numerical X

Specific Azimuth X Ranges X

dB Other

Graphic Contours

dB Other Does not contain internal graphics

ADDITIONAL COMMENTS: PC Based - FORTRAN 77

Provides for underwater explosion sources. Inputs made with DOS version 5 and above, while retaining ACE Editor capability if DOS-3 is used. A modified WXCORE translator for European raob code format is being completed.

Survey updated: 25 Aug 1994

NAME OF MODEL: BLASTX (is used for flat terrain)

DEVELOPER: ACTA, Inc

POINT OF CONTACT: Karl Overbeck

Address: Acta Inc, 505 North Orlando Ave
Cocoa Beach, FL 32931-3166

Phone Number: (407) 868-0508

Fax: (407) 783-8339

TYPE: Operational X Research Other

TYPE OF SOURCE: Point X

Above Ground Surface X Buried

Sonic Boom Moving on Surface

APPLICATIONS: Blast X Sonic Boom Moving Source on Surface
Other

LIMITATIONS:

THEORY: Ray Trace X Full Wave Empirical Other

METEOROLOGICAL INPUT: Sfc Temp Surface Winds Surface Pressure
Vert Temp Profile Vert Wind Profile
Rawin Data X Other Tower

OUTPUT UNITS: Overpressure in Pascals Overpressure in PSI X
Percent Broken Windows X
Other Expected casualties

OUTPUT TYPE: Numerical X
Specific Azimuth X Ranges X
dB Other
Graphic
Contours Limited
dB Other

ADDITIONAL COMMENTS: FORTRAN77: PC, CYBER 860

Survey updated: 29 Aug 94

NAME OF MODEL: BNOISE

DEVELOPER: US Army CERL Acoustic Team

POINT OF CONTACT: Michael J. White

Address: US Army Construction Engineering
Research Lab -ECA
PO Box 9005, Champaign, IL 61826

Phone Number: (800) 872-2375 ext 7436

Fax: (217) 373-7251

TYPE: Operational ☐ Research ☐ Other Envr Assessment

TYPE OF SOURCE: Point ☐
Above Ground ☐ Surface X Buried ☐
Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast X Sonic Boom ☐ Moving Source on Surface ☐
Other ☐

LIMITATIONS: ☐

THEORY: Ray Trace ☐ Full Wave ☐ Empirical X Other ☐

METEOROLOGICAL INPUT: Sfc Temp X Surface Winds X Surface Pressure ☐
Vert Temp Profile X Vert Wind Profile ☐
Rawin Data ☐ Other ☐

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other Sound exposure level in dB (change)

OUTPUT TYPE: Numerical X
Specific Azimuth ☐ Ranges X
dB X Other ☐
Graphic X
Contours X
dB ☐ Other ☐

ADDITIONAL COMMENTS:

Survey updated: 1 Sep 94

NAME OF MODEL: BOOM (Blast Operational Overpressure Model)

DEVELOPER: Donald A. Douglas (adapted from work by Richard Lorenz)

POINT OF CONTACT: Lt Col Roadcap

Address: PL/WE
Kirtland AFB NM 87117-6008

Phone Number: DSN 246-4722 Com (505) 846-4722

Fax: DSN 246-4394 Com (505) 846-4394

TYPE: Operational X Research Other

TYPE OF SOURCE: Point X

Above Ground X Surface X Buried

Sonic Boom Moving on Surface

APPLICATIONS: Blast X Sonic Boom Moving Source on Surface
Other

LIMITATIONS: Prediction Equation adjusted to fit Kirtland AFB data -- may not perform well at other areas.

THEORY: Ray Trace or Full Wave Empirical X Other

METEOROLOGICAL INPUT: Sfc Temp X Surface Winds X Surface Pressure X
Vert Temp Profile X Vert Wind Profile X
Rawin Data X Other Pibal Data

OUTPUT UNITS: Overpressure in Pascals X Overpressure in PSI
Percent Broken Windows
Other

OUTPUT TYPE: Numerical X
Specific Azimuth X Ranges X
dB Other

Graphic
Contours
dB Other

ADDITIONAL COMMENTS: PC Based - BASIC

Survey updated: 25 Aug 94

NAME OF MODEL: Crank Nicholson Parabolic Equation

DEVELOPER: Univ. of Mississippi

POINT OF CONTACT: Michael White

Address: US Army Construction Engineering Research Lab
PO Box 9005, Champaign, IL 61826-9005

Phone Number: 1-800-USA-CERL ext 7436

Fax: Com (217) 373-7251

TYPE: Operational ☐ Research ☒ Other ☐

TYPE OF SOURCE: Point ☒
Above Ground ☒ Surface ☒ Buried ☐
Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast ☐ Sonic Boom ☐ Moving Source on Surface ☒
Other ☒

LIMITATIONS: Less than 45° angle of propagation for source

THEORY: Ray Trace ☐ Full Wave ☒ Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☐ Surface Winds ☐ Surface Pressure ☐
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☐ Other ☐

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other Transmission loss (dB)

OUTPUT TYPE: Numerical ☐
Specific Azimuth ☐ Ranges ☐
dB ☒ Other 2D Transmission loss in height & range

Graphic ☐
Contours ☐
dB ☐ Other ☐

ADDITIONAL COMMENTS

Survey updated: 7 Sept 94

NAME OF MODEL: Green's Function Parabolic Equation (GFPE)

DEVELOPER: Pennsylvania State University

POINT OF CONTACT: David Marlin

Address: US Army Research Lab, Battlefield Environment
White Sands Missile Range, NM 88002-5501

Phone Number: DSN 258-5447 Com (505) 678-5447

Fax: DSN 258-8366 Com (505) 678-8366

TYPE: Operational ☐ Research ☒ Other ☐

TYPE OF SOURCE: Point ☒
Above Ground ☒ Surface ☒ Buried ☐
Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast ☐ Sonic Boom ☐ Moving Source on Surface ☒
Other ☒

LIMITATIONS: Less than 45° angle of propagation from source

THEORY: Ray Trace ☐ Full Wave ☒ Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☐ Surface Winds ☐ Surface Pressure ☐
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☐ Other ☒ (Pressure &
Humidity profiles)

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other Transmission Loss (dB)

OUTPUT TYPE: Numerical ☒
Specific Azimuth ☒ Ranges ☒
dB ☒ Other 2D Transmission Loss in Height & Range

Graphic ☐
Contours ☐
dB ☒ Other ☐

ADDITIONAL COMMENTS: Models turbulence in upward radiative atmosphere

Survey updated: 9 Sept 94

NAME OF MODEL: HARPA

DEVELOPER: Wave Propagation Lab

POINT OF CONTACT: Tom Georges

Address: NOAA WPL
325 Broadway, Boulder, CO 80303

Phone Number: (303) 497-6437

Fax: (303) 497-3577

TYPE: Operational X Research X Other

TYPE OF SOURCE: Point X

Above Ground X Surface X Buried
Sonic Boom Moving on Surface

APPLICATIONS: Blast X Sonic Boom Moving Source on Surface
Other any point source

LIMITATIONS: Geometrical acoustics

THEORY: Ray Trace X Full Wave Empirical Other

METEOROLOGICAL INPUT: Sfc Temp Surface Winds Surface Pressure
Vert Temp Profile X Vert Wind Profile X
Rawin Data Other 3D temp & wind field

OUTPUT UNITS: Overpressure in Pascals Overpressure in PSI
Percent Broken Windows
Other None

OUTPUT TYPE: Numerical
Specific Azimuth X Ranges X
dB Other range vs. time, range vs. elev. angle,
eigen rate finder, machine readable points
Graphic X
Contours
dB Other Computes ray paths

ADDITIONAL COMMENTS: Ray trace caustics only, no transmission losses are calculated. Complete documentation available with source code in FORTRAN (downloadable by FTP). Underwater version available)

Survey updated: 25 Aug 94

NAME OF MODEL: HI-PE

DEVELOPER: University of Salford

POINT OF CONTACT: Martin West or Geoff Kerry

Address: University of Salford
Salford M5 4WT UK

Phone Number: (from US) 44-61-745-5582

Fax: (from US) 44-61-745-5427

TYPE: Operational ☐ Research ☒ Other ☐

TYPE OF SOURCE: Point ☒

Above Ground ☒ Surface ☒ Buried ☐

Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast ☒ Sonic Boom ☐ Moving Source on Surface ☐
Other Continuous source

LIMITATIONS: ☐

THEORY: Ray Trace ☐ Full Wave ☒ Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☒ Surface Winds ☒ Surface Pressure ☐
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☐ Other ☐

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other Peak SPL dB versus distance

OUTPUT TYPE: Numerical ☐
Specific Azimuth ☒ Ranges ☐
dB ☒ Other ☐

Graphic ☐
Contours ☐
dB ☐ Other ☐

ADDITIONAL COMMENTS: PC based FORTRAN77
Requires SALFORD SOFTWARE FTN77 compiler
and GTEK7 graphics library

Survey updated: 21 Sept 94

NAME OF MODEL: KNAPS (Kirtland Noise Assessment and Prediction System)

DEVELOPER: WSMR's ASL (Modified NAPS Model)

POINT OF CONTACT: John Noble

Address: US Army Research Lab, AMSRL-BE-S
White Sands Missile Range, NM 88002-5501

Phone Number: DSN 258-3751 Com (505) 678-3751

Fax: DSN 258-8366 Com (505) 678-8366

TYPE: Operational X Research X Other

TYPE OF SOURCE: Point X

Above Ground X Surface X Buried

Sonic Boom Moving on Surface

APPLICATIONS: Blast X Sonic Boom Moving Source on Surface
Other

LIMITATIONS:

THEORY: Ray Trace X Full Wave Empirical Other

METEOROLOGICAL INPUT: Sfc Temp X Surface Winds X Surface Pressure X
Vert Temp Profile X Vert Wind Profile X
Rawin Data X Other Relative Humidity

OUTPUT UNITS: Overpressure in Pascals Overpressure in PSI
Percent Broken Windows
Other Ray trace trajectories at a given azimuth.
Surface plots (sound contours) in dB.

OUTPUT TYPE: Numerical X
Specific Azimuth X Ranges X
dB X Other

Graphic X
Contours Vertical/Horizontal Plots
dB X Other Ray trace trajectory plots

ADDITIONAL COMMENTS: Great Internal Graphics. PC based - FORTRAN 77

Survey updated: 13 Sep 94

NAME OF MODEL: LARKHILL

DEVELOPER: University of Salford

POINT OF CONTACT: Geoff Kerry

Address: University of Salford
Salford M5 4WT UK

Phone Number: (from US) 44-61-745-5582

Fax: (from US) 44-61-745-5427

TYPE: Operational ☒ Research ☐ Other ☐

TYPE OF SOURCE: Point ☒

Above Ground ☒ Surface ☒ Buried ☐

Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast ☒ Sonic Boom ☐ Moving Source on Surface ☐
Other ☐

LIMITATIONS: ☐

THEORY: Ray Trace ☒ Full Wave ☐ Empirical ☒ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☒ Surface Winds ☒ Surface Pressure ☐
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☒ Other ☐

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other ☐ 360 Surface Distribution Map of Sound
Levels in dB -- Hand Contouring Required.

OUTPUT TYPE: Numerical ☐
Specific Azimuth ☐ Ranges ☐
dB ☐ Other ☐

Graphic ☒
Contours ☐
dB ☒ Other ☐

ADDITIONAL COMMENTS: PC based BASIC

Survey updated: 21 Sept 94

NAME OF MODEL: LARRIAPPS

DEVELOPER: University of Salford

POINT OF CONTACT: Martin West or Geoff Kerry

Address: University of Salford
Salford M5 4WT UK

Phone Number: (from US) 44-61-745-5582

Fax: (from US) 44-61-745-5427

TYPE: Operational X Research Other

TYPE OF SOURCE: Point X

Above Ground X Surface X Buried

Sonic Boom Moving on Surface

APPLICATIONS: Blast X Sonic Boom Moving Source on Surface
Other

LIMITATIONS: Flat Land

THEORY: Ray Trace X Full Wave Empirical X Other

METEOROLOGICAL INPUT: Sfc Temp X Surface Winds X Surface Pressure
Vert Temp Profile X Vert Wind Profile X
Rawin Data X Other

OUTPUT UNITS: Overpressure in Pascals Overpressure in PSI
Percent Broken Windows
Other Peak SOL dB

OUTPUT TYPE: Numerical
Specific Azimuth X Ranges
dB X Other

Graphic X
Contours X
dB X Other High quality radial contouring

ADDITIONAL COMMENTS: PC based FORTRAN77
Requires SALFORD SOFTWARE FTN77 and
GTEK7 graphics library

Survey updated: 21 Sept 94

NAME OF MODEL: LAP (Livermore Atmospheric Propagation) Code

DEVELOPER: Modified CIPS Cods

POINT OF CONTACT: Sang Wook Kang

Address: L-194 Lawrence Livermore Lab
Livermore, CA 94550

Phone Number: (510) 422-7233

Fax: (510) 422-5397

TYPE: Operational ☐ Research ☒ Other ☐

TYPE OF SOURCE: Point ☒
Above Ground ☐ Surface ☒ Buried ☐
Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast ☒ Sonic Boom ☐ Moving Source on Surface ☐
Other ☐

LIMITATIONS: ☐

THEORY: Ray Trace ☒ Full Wave ☐ Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☒ Surface Winds ☒ Surface Pressure ☐
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☐ Other ☐

OUTPUT UNITS: Overpressure in Pascals ☒ Overpressure in PSI ☒
Percent Broken Windows ☐
Other ☐

OUTPUT TYPE: Numerical ☐
Specific Azimuth ☐ Ranges ☐
dB ☐ Other ☐
Graphic ☒
Contours ☐ Plots ray traces (can plot any azimuth direction)
dB ☐ Other ☐

ADDITIONAL COMMENTS: LAP used with BLASTO. Runs on CRAY or VAX.
Prints out sonic speeds. Identifies focus points.

Survey updated: 29 Aug 94

NAME OF MODEL: Low Frequency Long Range Acoustic Propagation
Prediction Subroutine

DEVELOPER: Georgia Tech Research Institute

POINT OF CONTACT: Arnold W. Mueller

Address: NASA, Langley Research Center
Hampton, VA 23681

Phone Number: (804) 864-5277

Fax: (804) 864-8290

TYPE: Operational ☐ Research ☒ Other ☐

TYPE OF SOURCE: Point ☒

Above Ground ☒ Surface ☐ Buried ☐

Sonic Boom ☐ Moving on Surface ☐

It estimates the losses sustained by an acoustic signal propagation over tens of kilometers. It is based on the use of "look-up" tables for 528 different combinations of signals interpolated between 8 unique frequencies (8.0, 16.0, 31.5, 63.0, 125.0, 500.0, or 1000.0 Hz); propagating over grass or desert; for weather profile type of lapse, ground inversion, or elevated inversion; for 0, +12, or -12 knots of wind speed at source heights of 5, 30, 135, 150, or 300 meters.

APPLICATIONS: Blast ☐ Sonic Boom ☐ Moving Source on Surface ☐
Other ☒

LIMITATIONS: Requires input to be interpolated between 8 frequencies
and 3 weather profiles. Does not have isothermal or wind
lapse case.

THEORY: Ray Trace ☐ Full Wave ☒ Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☐ Surface Winds ☐ Surface Pressure ☐
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☐ Other ☐

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other standard reference acoustic pressure

OUTPUT TYPE: Numerical ☒
Specific Azimuth ☐ Ranges ☐
dB ☒ Other ☐
Graphic ☐
Contours ☐
dB ☐ Other ☐

ADDITIONAL COMMENTS: Detailed operational information may be obtained from Charles D. Smith, Lockheed Engineering & Sciences, c/o NASA Langley Research Center (804-864-5275)

Survey updated: 15 Sep 94

NAME OF MODEL: NAPS (Noise Assessment and Prediction System)

DEVELOPER: WSMR's ASL

POINT OF CONTACT: John Noble

Address: US Army Research Lab, AMSRL-BE-S
White Sands Missile Range, NM 88002-5501

Phone Number: DSN 258-3751 Com (505) 678-3751

Fax: DSN 258-8366 Com (505) 678-8366

TYPE: Operational ☒ Research ☒ Other ☐

TYPE OF SOURCE: Point ☒

Above Ground ☒ Surface ☒ Buried ☐

Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast ☒ Sonic Boom ☐ Moving Source on Surface ☐
Other ☐

LIMITATIONS: ☐

THEORY: Ray Trace ☒ Full Wave ☐ Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☒ Surface Winds ☒ Surface Pressure ☒
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☒ Other Relative Humidity

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other Ray trace trajectories at a given azimuth.
Surface plots (sound contours) in dB.

OUTPUT TYPE: Numerical ☒
Specific Azimuth ☒ Ranges ☒
dB ☒ Other ☐

Graphic ☒
Contours Vertical/Horizontal Plots
dB ☒ Other Ray trace trajectory plots

ADDITIONAL COMMENTS: Great Internal Graphics. PC based - FORTRAN 77
Has terrain.

Survey updated: 13 Sep 94

NAME OF MODEL: NIFD/PE

DEVELOPER: West Point Military Academy

POINT OF CONTACT: LTC Jack Robertson

Address: US Military Academy, Dept of Mathematics
West Point, NY 10996-1787

Phone Number: DSN 688-2453 Com (914) 938-2453

Fax: DSN 688-2409 Com (914) 938-2409

TYPE: Operational ☐ Research ☒ Other ☐

TYPE OF SOURCE: Point ☐
Above Ground ☐ Surface ☒ Buried ☐
Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast ☒ Sonic Boom ☐ Moving Source on Surface ☐
Other Continuous source

LIMITATIONS: ☐

THEORY: Ray Trace ☐ Full Wave ☒ Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☐ Surface Winds ☐ Surface Pressure ☐
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☐ Other ☐

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other Sound pressure level in dB

OUTPUT TYPE: Numerical ☒
Specific Azimuth ☐ Ranges ☒
dB ☒ Other ☐

Graphic ☒
Contours ☐
dB ☒ Other ☐

ADDITIONAL COMMENTS:

Survey updated: 14 Sep 94

NAME OF MODEL: PC BOOM3: Single Event Sonic Boom Model

DEVELOPER: Wyle Laboratories

POINT OF CONTACT: Micah Downing

Address: AL/OEBN, 2610 Seventh Street
Wright-Patterson AFB, OH 45433-7901

Phone Number: DSN 785-3664 Com (513) 255-3664

Fax: DSN 986-7680 Com (513) 476-7680

TYPE: Operational X Research X Other

TYPE OF SOURCE: Point
Above Ground Surface Buried
Sonic Boom X Moving on Surface

APPLICATIONS: Blast Sonic Boom X Moving Source on Surface
Other

LIMITATIONS:

THEORY: Ray Trace X Full Wave Empirical Other

METEOROLOGICAL INPUT: Sfc Temp Surface Winds Surface Pressure
Vert Temp Profile X Vert Wind Profile X
Rawin Data Other

OUTPUT UNITS: Overpressure in Pascals X (& psf) Overpressure in PSI
Percent Broken Windows
Other Overpressure in C-weighted Sound Exposure
Level (CSEL) in dB

OUTPUT TYPE: Numerical X
Specific Azimuth Ranges
dB X Other or psf
(CSEL)
Graphic X
Contours X (& Footprints)
dB X Other psf or Pa
(CSEL)

ADDITIONAL COMMENTS: Written in FORTRAN 77. PC based program.
386 or higher with math coprocessor recommended.
Menu based used interface.

Survey updated: 29 Aug 94

NAME OF MODEL: RAYTR

DEVELOPER: Penn State University

POINT OF CONTACT: Dr Dennis Thomson, Dept of Meteorology

Address: 503 Walker Bldg

Penn State University

University Park, PA 16802

Phone Number: (814) 865-0478

Fax: (814) 865-3663

TYPE: Operational ☐ Research ☒ Other ☐

TYPE OF SOURCE: Point ☐

Above Ground ☒

Surface ☒ Buried ☐

Sonic Boom ☐

Moving on Surface ☒

APPLICATIONS: Blast ☒ Sonic Boom ☐ Moving Source on Surface ☒

Other ☐

LIMITATIONS: ☐

THEORY: Ray Trace ☒ Full Wave ☐ Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☒ Surface Winds ☒ Surface Pressure ☐

Vert Temp Profile ☒ Vert Wind Profile ☒

Rawin Data ☒ Other Sfc RH and vert profile
of RH

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐

Percent Broken Windows ☐

Other sound pressure levels in dB

OUTPUT TYPE: Numerical ☒

Specific Azimuth ☒

Ranges ☒

dB ☒ Other ☐

Graphic ☒

Contours of sound pressure levels at fixed times

dB ☒ Other ☐

ADDITIONAL COMMENTS: Can be used for one or more sources on or above the ground. Inputs also include the 2D topography and arrays of surface temperature, wind and relative humidity. Output is time dependent sound pressure levels in dB at specified locations in the grid. Software dated, output capability current.

Survey updated: 29 Aug 94

NAME OF MODEL: Scanning Fast Field Program (SCAFFIP)

DEVELOPER: US Army Research Lab -- Battlefield Environment

POINT OF CONTACT: Dr. John Noble

Address: US Army Research Lab
Battlefield Environment
AMSRL-BE-S
White Sands Missile Range, NM 88002-5501

Phone Number: DSN 258-3751 Com (505) 678-3751

Fax: DSN 258-8366 Com (505) 678-8366

TYPE: Operational ☐ Research ☒ Other ☐

TYPE OF SOURCE: Point ☒

Above Ground ☒ Surface ☒ Buried ☐

Sonic Boom ☐ Moving on Surface ☐

APPLICATIONS: Blast ☒ Sonic Boom ☐ Moving Source on Surface ☒
Other ☐

LIMITATIONS: ☐

THEORY: Ray Trace ☐ Full Wave ☒ Empirical ☐ Other ☐

METEOROLOGICAL INPUT: Sfc Temp ☐ Surface Winds ☐ Surface Pressure ☐
Vert Temp Profile ☒ Vert Wind Profile ☒
Rawin Data ☐ Other Vert. Pressure & Humidity
Profile

OUTPUT UNITS: Overpressure in Pascals ☐ Overpressure in PSI ☐
Percent Broken Windows ☐
Other Transmission Loss (dB)

OUTPUT TYPE: Numerical ☐
Specific Azimuth ☒ Ranges ☒
dB ☒ Other 360° scan in fixed azimuth increments

Graphic ☐
Contours ☐
dB ☐ Other ☐

ADDITIONAL COMMENTS:

Survey updated: 8 Sept 94

NAME OF MODEL: Sound Prop

DEVELOPER: US Army CERL Acoustic Team

POINT OF CONTACT: Michael J. White

Address: US Army Construction Engineering Research Lab
PO Box 9005, Champaign IL 61826-9005

Phone Number: (217) 352-6511 ext 7436

Fax: (217) 373-7251

TYPE: Operational X Research X Other Environmental Assessment

TYPE OF SOURCE: Point X

Above Ground X

Surface X Buried X

Sonic Boom

Moving on Surface

APPLICATIONS: Blast X Sonic Boom Moving Source on Surface
Other Continuous Wave (Either)

LIMITATIONS:

THEORY: Ray Trace Full Wave Empirical Other X

METEOROLOGICAL INPUT: Sfc Temp X Surface Winds X Surface Pressure
Vert Temp Profile X Vert Wind Profile X
Rawin Data X Other

OUTPUT UNITS: Overpressure in Pascals Overpressure in PSI
Percent Broken Windows
Other dB

OUTPUT TYPE: Numerical X
Specific Azimuth X Ranges
dB X Other 1/3 Octave Spectrum

Graphic X

Contours

dBX Other 1/3 Octave Spectrum

ADDITIONAL COMMENTS: Allows for a barrier, and for an arbitrary source spectrum

Survey updated: 7 Sept 94

REFERENCES

REFERENCES USED IN THIS CATALOG

American National Standards Institute (ANSI), Airblast Characteristics for Single Point Explosions in Air, with a Guide to Evaluation of Atmospheric Propagation and Effects, ANSI S2.20-1983, Acoustical Society of America, New York, NY, 1983.

Event DIAL PACK Preliminary Report--Volume 1, DASA 2606-I (DASIAC SR-115), DASIAC, General Electric-TEMPO, Santa Barbara, CA, May 1971.

Gould, Kenneth E., High Explosion Field Tests: Explosion Phenomena and Environmental Impacts, DNA 6187F (performed by Kaman Tempo), 1 October 1981.

Single Point Explosions in Air, American National Standards Institute; Committee on Mechanical Vibrations and Shock, S-2; Working Group, Atmospheric Blast Effects, S-2-54; Reed, J.W., Chairman; 20 July 1976 draft report.

Vortman, L.J., Explosive Cratering Experiments, Report SCR-406, Sandia Laboratories, Albuquerque, NM, May 1961.

OTHER REFERENCES

American National Standards Institute (ANSI), Metric Practice Guide E, ANSI Z210.1, American Society for Testing Materials, Philadelphia, PA, 1974.

Baker, W.E., Explosions in Air, Univ. Texas Press, Austin, TX, 1973.

Bell, W.B., "Animal Response to Sonic Booms," The Journal of the Acoustical Society of America, Vol. 51, No. 2 (Part 3):758-765, February 1972.

Bowen, I.G., et al., Translational Effects of Air Blast from High Explosives, DASA 1336, Lovelace Foundation for Medical Education and Research, Albuquerque, NM, 7 November 1962.

Bowen, I.G., et al., Translational Effects of Blast Waves, DA-49-146-XZ-055, Lovelace Foundation for Medical Education and Research, Albuquerque, NM, 11 March 1963.

Civil Aircraft Sonic Boom Regulation (Final EIS), EIS-AA-73-0115-F, Federal Aviation Administration, Washington, DC, January 1973.

Cox, E.F., H.J. Plagge, & J.W. Reed, "Meteorology Directs Where Blast Will Strike," Bulletin of the American Meteorological Society, 35, 95-103, March 1954.

Damon, E.G., et al., The Tolerance of Birds to Airblast, DNA 3314F, Director, Defense Nuclear Agency, Washington, DC, July 1974.

Dewey, J.M., "The Propagation of Sound from the Eruption of Mt. St. Helens on 18 May 1980," Northwest Science, 59, 2, 79-92, 1985.

Fairfield, C., "The Acoustic Effects of Mount St. Helens Eruption on May 18, 1980" Oregon Geology, 42, 200-202, 1980.

Fletcher, E.G., et al., Determinations of Aerodynamics-Drag Parameters of Small Irregular Objects by Means of Drop Tests, CEX-59.14, Lovelace Foundation for Medical Education and Research, Albuquerque, NM, June 1960.

Gesswein, J., and P. Carrao, The Position of Eardrum Rupture and Hearing Loss in the Scale of Injuries from Nuclear Blast, NSCDC 3789, Naval Ship Research and Development Center, Bethesda, MD, February 1972.

Glasstone, S., and P.J. Dolan, The Effects of Nuclear Weapons, U.S. Government Printing Office, Washington, DC, 1977.

Heaps, C.W., K.S. Fansler, & E.M. Schmidt, "Computer Implementation of a Muzzle Blast Prediction Technique," Shock & Vibration Bulletin, 56, 1, Naval Research Laboratory, Washington, DC, August 1986.

Information on Levels of Environmental Noise Requisite to Protect Public Health and Welfare With an Adequate Margin of Safety, 550/9-74-004, U.S. Environmental Protection Agency, Office of Noise Abatement and Control, U.S. Government Printing Office, Washington, DC, March 1974.

Keefer, J.H., & J.D. Day, "Terrain Effects on Blast Wave Parameters," Report BRL-1319, U.S. Army Ballistic Research Laboratories, Aberdeen Proving Ground, MD, April 1966.

Maglieri, D.J., V. Huckle, and T.L. Parrott, Ground Measurements of Shock-Wave Pressure for Fighter Airplanes Flying at Very Low Altitudes and Comments on Associated Response Phenomena, NASA TN-E-3443, Langley Research Center, Langley Station, Hampton, VA, July 1966.

Morris, P.J., Forest Blowdown From Nuclear Airblast, DNA 3054F (USR 7049-10, Rev. 1), URS Research Company, San Mateo, CA, July 1973.

Nicholls, H.R., C.F. Johnson, and W.I. Duvall, Blasting Vibrations and Their Effects on Structures, Bureau of Mines Bulletin 656, U.S. Department of the Interior, Washington, DC, 1971.

Nixon, C.W., Proceedings of Noise as a Public Hazard, ASHA #4, February 1969.

Nixon, E.W., H.K. Hille, H.C. Sommer, and E. Guild, Sonic Booms Resulting from Extremely Low-Altitude Supersonic Flight: Measurements and Observation on Houses, Livestock and People, AMRL-TR-68-52, Aerospace Medical Research Laboratories, Aerospace Medical Division, Air Force Systems Command, Wright-Patterson Air Force Base, OH, October 1968.

"Occupational Noise Exposure," Code of Federal Regulations, Title 29, Paragraph 1910-95, pp 220-221, Rev. January 1, 1972.

Overbeck, K., "Updated Documentation for the Correlated Blast Damage Assessment Model," Tech. Report No. 86-3145.09, NTS Engineering, Long Beach, CA, October 1986.

Pater, L.L., "Gun Blast Far Field Peak Overpressure Contours," Report TR 79-442, Naval Surface Weapons Center, Silver Spring, MD, March 1981.

Perkins, B. Jr., P.H. Lorrain, & W.F. Jackson, "Handbook for Prediction of Air Blast Focusing," Report BRL-1118, Ballistic Research Laboratories, Aberdeen Proving Ground, MD, October 1960.

Pickering, E.E., and J.L. Bockholt, Probabilistic Air Blast Failure Criteria for Urban Structures, SRI Project 6300, Stanford Research Institute, Menlo Park, CA, November 1971.

RCC-MG (Range Commanders Council - Meteorological Group), "Meteorological Data Error Estimates," Document 353-81, White Sands Missile Range, NM, 1981.

Reed, J.W., "Explosion Wave Amplitude Statistics for a Caustic at Ranges of 30 to 45 Miles," Report SC-RR-67-860, Sandia Laboratories, Albuquerque, NM, February 1968.

Reed, J.W., Acoustic Wave Effects Project: Airblast Prediction Techniques, SC-M-69-332, Sandia Laboratories, Albuquerque, NM, 1969.

Reed, J.W., "Blast Predictions and Microbarograph Measurements, Project MIDDLE GUST," Report SLA-73-0484, Sandia Laboratories, Albuquerque, NM, August 1973.

Reed, J.W., Simplified Blast Nuisance Predictions for Small Explosions, Sandia Laboratories, Albuquerque, NM, 9 July 1974.

Reed, J.W., "Project MISTY CASTLE - Distant Airblast Effects Predictions," Report SAND78-0271, Sandia Laboratories, Albuquerque, NM, August 1978.

Reed, J.W., "Predictions of Nuisance Damage and Hazard from Accidental Explosions During Trident Missile Test Flights," Report SAND79-0626, Sandia National Laboratories, Albuquerque, NM, March 1980a.

Reed, J.W., "Climatological Assessment of Airblast Propagations from Explosion Tests at White Sands Missile Range," Report SAND86-1346, Sandia National Laboratories, Albuquerque, NM, August 1986.

Reed, J.W., "Analysis of the Accidental Explosion of PEPCON, Henderson, Nevada, May 4, 1988," Report SAND88-2902, Sandia National Laboratories, Albuquerque, NM, November 1988.

Reed, J.W., "Program "Blasto" for Weather-Dependent Airblast Predictions" in Minutes, 24th DOD Explosive Safety Seminar, St Louis, MO, August 26-31, 1990b

Reed, J.W., & H.W. Church, "MINOR SCALE Weather-Watch & Microbarograph Project," in Proc. MINOR SCALE Results Symp., Vol. 2, Field Command Defense Nuclear Agency, Albuquerque, NM, 30 May 1986.

Reed, J.W., H.W. Church, & T.W. Huck, "MISTY PICTURE Weather-Watch & Microbarograph Project," in Proc. MISTY PICTURE Results Symp., Defense Nuclear Agency, Washington, DC, 7-10 December 1987.

Richmond, D.R., et al., The Relationship between Selected Blast-Wave Parameters and the Response of Mammals Exposed to Air Blast, DASA 1860, Lovelace Foundation for Medical Education and Research, Albuquerque, NM, November 1966.

Richmond, D.R., et al., "Blast Biophysics: Past, Present and Future," Proceedings of the MISERS BLUFF Phase II Results Symposium, 27-29 March 1979, Volume III, POR 7013-3, Defense Nuclear Agency, 29 September 1979.

Richmond, D.R., et al., Tertiary Blast Effects: The Effects of Impact on Mice, Rats, Guinea Pigs and Rabbits, DASA 1245, Lovelace Foundation for Medical Education and Research, Albuquerque, NM, 28 November 1961.

Rothwell, P., "Calculation of Sound Rays in the Atmosphere," J. Acoust. Soc. Amer., 19, 1, 1947.

Soo Hoo, G., "Gun Blast Experiments with an 8"/51 Gun," Tech. Note TN-T-1/15, Naval Surface Weapons Center, Dahlgren, VA, February 1975.

Soo Hoo, G., & G. Moore, "Scaling of Naval Gun Blast Peak Overpressures," Tech. Note TN-T7/72, Naval Surface Weapons Center, Dahlgren, VA, August 1972.

Swisdak, M.M., Jr., "Explosions Effects and Properties," Report NSWC/NOL/TR-75-116, Naval Surface Weapons Center, Silver Spring, MD, October 1975.

The Effects of Sonic Boom and Similar Impulsive Noise on Structures, NTID300.12, U.S. Environmental Protection Agency, Washington, DC, December 31, 1971.

Thompson, R.J., "Ray Theory for an Inhomogeneous Moving Medium," J. Acoust. Sci. Amer., 51, 1685-1682, 1972.

Wanner, J.L., J. Vallee, C. Vivier, & C. Thery, "Theoretical and Experimental Studies of Focus of Sonic Booms," J. Acoust. Soc. Amer., 52, 1, (Pt 1), July 1972.

Warren, C.H.E., 'Recent Sonic-Bang Studies in the United Kingdom," Journal of the Acoustical Society of America, Vol. 51, No. 2 (Part 3); 783-788, February 1972.

Weber, G., "Sonic Boom Effects 11.1: Structure and Terrain," Journal of Sound and Vibration, Vol. 20, No. 4:531-534, 1972.

White, C.S., et al., The Biodynamics of Airblast, DNA 2738T, Lovelace Foundation for Medical Education and Research, Albuquerque, NM, 1 July 1971.

Wiggins, J.H., Jr., "Sonic Boom Damage to Structures," Institute of Environmental Science, 1969 Proceedings, 15 Annual Technical Meeting--Man in His Environment, 20-24 April 1969, Anaheim, CA, Institute of Environmental Sciences, Mt. Prospect, IL, pp 189-197.

Wiggins, J.H., Jr, Effect of Sonic Boom, J.H. Wiggins Company, Palos Verdes Estates, CA, 1969.

Wilton, C., and B. Gabrielsen, Summary Report: House Damage Assessment, DNA 2906F, Headquarters, Defense Nuclear Agency, Washington, DC, January 1973.

WMO (World Meteorological Organization), Guide to Meteorological Instrument and Observing Practices, 4th Ed., WMO-No.8.TP.3, WMO Secretariat, Geneva, Switzerland, 1971.

Yagla, J.J., "16-in Gun Blast and the Battleship Reactivation Program," Naval Engineers Journal, 99, 3, 227-238, May 1987.